

abi Elite Lectern

Stylish Modern Lectern

The new Elite lectern is modern, stylish and functional. It has aluminium uprights with hardened safety glass base, upright panel and top platen. The aluminium uprights are available in powdercoated silver or black.

The Elite lectern includes a condenser microphone and on/off switch. It also includes a low voltage light with on/off switch, and 12V DC power adaptor.

An XLR socket is provided at the base of the lectern to carry the microphone signal to the room's amplifier and speaker system.

The gooseneck microphone, gooseneck light, 5m XLR cable and power supply are supplied as part of the Lectern package.

The Elite Lectern provides a strong focal point for the presentation – it helps focus the audience on the Presenter.

Smart & eye catching the Elite lectern will enhance your auditorium or training room. It can be dismantled easily for storage or transport. Available with silver uprights and clear hardened safety glass panels, or black uprights with smoky tint hardened safety glass panels.



Details:

Construction:

<i>Frame:</i>	Powdercoated aluminium extrusion
<i>Front Panel:</i>	12mm hardened safety glass (clear or smoky tint)
<i>Base Plate:</i>	12mm hardened safety glass (clear or smoky tint)
<i>Top Platen:</i>	12mm hardened safety glass with glass lip (clear or smoky tint)
<i>Note:</i>	12mm acrylic can be substituted for glass if required

Connections:

<i>Microphone:</i>	XLR Socket (top left platen) for microphone input XLR Socket (lower left aluminium upright) for audio out
<i>Light:</i>	XLR socket for light attachment
<i>Power:</i>	12V DC input (for light) Battery compartment (2 x AA batteries) for microphone power

Controls:

<i>Microphone:</i>	On/Off switch for microphone (top left aluminium upright)
<i>Light:</i>	On/Off switch on light

Specifications:

<i>Height:</i>	1100mm
<i>Width:</i>	550mm
<i>Weight:</i>	26kg (hardened safety glass)
<i>Inclusions:</i>	Condenser gooseneck microphone, low voltage gooseneck light, 12V DC power supply, 5m XLR/6.3mm cable, manual, 2 x AA batteries



CE

FC