

# abi Elite Lectern

STYLISH MODERN LECTERN

ELITES - Silver frame - clear glass  
ELITEB - Black frame - smoky tint glass  
ELITEG - Gold frame - smoky tint glass

**T**HE NEW ELITE lectern is modern, stylish and functional. It has aluminium uprights with hardened safety glass base, upright panel and top platen. Aluminium uprights are available in powdercoated silver or black.

The Elite lectern includes a condensor microphone and on/off switch. It also includes a low voltage light with on/off switch, and 12V DC power adaptor.

An XLR socket is provided at the base of the lectern to carry the microphone signal to the room's amplifier and speaker system.

The gooseneck microphone, gooseneck light, 5m XLR cable and power supply are supplied as part of the Lectern package.

The Elite Lectern provides a strong focal point for the presentation – it helps focus the audience on the Presenter.

Smart & eye catching the Elite lectern will enhance your auditorium or training room. It can be dismantled easily for storage or transport.

Available with silver uprights and clear hardened safety glass panels, or black uprights with smoky tint hardened safety glass panels.



## SPECIFICATIONS

### Construction

**Frame:** Powdercoated aluminium extrusion  
**Front Panel:** 12mm hardened safety glass (clear or smoky tint)  
**Base Plate:** 12mm hardened safety glass (clear or smoky tint)  
**Top Platen:** 12mm hardened safety glass with glass lip (clear or smoky tint)

### Connections

**Microphone:** XLR Socket (Platen top left) for gooseneck microphone input  
XLR Socket (Aluminium upright lower left - upper) for audio out, using bypass mic. connection  
RCA Socket (Aluminium upright lower left - lower) for optional wireless mic., using wireless receiver connection  
**Light:** XLR socket for light attachment  
**Power:** 12V DC input (for light)  
Battery compartment (2 x AA batteries) for microphone power

### Controls

**Microphone:** On/Off switch for microphone (top left aluminium upright)  
On/Off switch for wireless microphone system  
Volume control wireless microphone Channel 1  
Volume control wireless microphone Channel 2  
**Light:** On/Off switch on light

### Dimensions

**Height:** 1100mm  
**Width:** 550mm  
**Weight:** 26kg (hardened safety glass)

### Inclusions

Condensor gooseneck microphone, low voltage gooseneck light.  
12V DC power supply, 5m XLR/6.3mm cable, manual, 2 x AA batteries

### Optional

Wireless handheld microphone, wireless microphone receiver.  
Top Platen with touchscreen monitor & PC connections in aluminium upright



Distributed by: ABI China Ltd. 8F/122-124 Connaught Rd, Central, HONG KONG

Tel: 852.2543 8420 Fax: 852.2544 9359. Email: info@abichina.com

Website: www.abichina.com

**abi**  
abichina Ltd