

TOUCH



IC200



Multimedia Room Controller/Switcher



Notebook connections on face under push/pull cover



Multifunction & multi-connector interface; includes projector & screen control & mic over-ride



TOUCH IC200

Item	Type	Description	Qty	Specifications
1	Audio Input	3.5mm socket	1	-10db/1k Ω /20Hz-20kHz
		L/R RCA socket	3	-10db/1k Ω /20Hz-20kHz
2	Audio Output	L/R RCA socket	1	-10db/1k Ω /20Hz-20kHz
3	Video Input	RCA socket	3	0.5V-1Vp/75 Ω /100MHz(-3db)
4	Video Output	RCA socket	1	0.5V-1Vp/75 Ω /100MHz(-3db)
5	Data Input	15pin HDD female	3	0.5V-1Vp-p/75 Ω /300MHz(-3db)
6	Data Output	15pin HDD female	2	0.7V-1Vp-p/75 Ω /300MHz(-3db)
7	RS232 Program	9pin DSub female	1	Transfer data setting
8	RS232 Control	9pin DSub female	0	Baud rate 600-115200, Parity error (No/odd/even parity), data 6,7,8 bit
9	MIC Input	6.3mm	1	600 Ω /20Hz - 20kHz
10	Infra-Red Control	Ind Std 2PIN port	1	IR: Middle frequency self adjusting
11	Digital I/O	Ind Std 2PIN port	1	TTL level standard
12	Network Port	RJ45	1	Direct Contact
13	USB Port	USB A socket	1	Direct Contact
14	Line-in Vol adjust	Potentiometer adjust	1	B100K
15	Proj Power Out	International socket	1	AC220/240V 10A
16	Motor Scr Up/Dn	Ind Std 2PIN port	1	TTL level standard
17	Power Input	IEC socket	1	AC220/240V 10A 50Hz
18	Power Consumption			AC220/240V 10A
19	Weight			6.6W
20	Dimensions			235 (L) x 130 (W) x 110 (H) mm
21	Operating Temp			0-40°C; 5-85% Humidity (No Dew)

abichina

Distributed by: ABI China Ltd. 8F/122-124 Connaught Rd, Central, HONG KONG
 Tel: 852.2543 8420 Fax: 852.2544 9359 Email: info@abichina.com
 www.abichina.com