



TOUCH

LCD TOUCHSCREEN CONTROL SYSTEM



NC600

- Wireless LCD Touchscreen Control System with built-in Switcher function
- ISP, SSP program technology offering advanced functions
- LAN connectivity; can be managed by remote Control Center & can communicate with internet
- System will function if LAN network not functioning
- Switching function for 3xVGA, 3xVideo, 5 x Audio. Turns on 3 devices & controls projection screen; I/R and Relay controls.



TOUCH

NG600

Serial	Name	Port Type	Number	Characteristics
1	Audio input	3.5mm stereo	5	-10db/1k \bar{U} /20Hz-20kHz
2	Audio output	3.5mm stereo	2	-10db/1k \bar{U} /20Hz-20kHz
3	Analog RGB input	15pinHD female	3	0.5V-1Vp-p/75 \bar{U} /300MHz(-3db)
4	Analog RGB output	15pinHD female	2	0.7V-1Vp-p/75 \bar{U} /300MHz(-3db)
5	Composite video input	RCA	3	0.5V-1Vp/75 \bar{U} /100MHz(-3db)
6	Composite video output	RCA	2	0.7V-1Vp/75 \bar{U} /100MHz(-3db)
7	RS232 program port	DSUB9pin	1	Transfer setting data
8	One-way RS232 control output	Use together with RS232 port	4	Baud rate(600-115200), Parity error (No parity, odd parity, even parity), data bit(5,6,7,8 bit)
9	Infra-red control	Industry standard 2PIN port	4	IR: Middle frequency self-adjusting
10	Digital I/O	Industry standard 2PIN port	4	TTL level standard
11	MIC input	6.3mm	1	600 \bar{U} /20Hz-20kHz
12	Network port	RJ45	1	100M/10M
13	IC card control port	RJ45	1	Connect IC card control RS485
14	Visual and Audible siren port	RJ45	1	Connect siren
15	Line-in volume adjust	12 level digital volume adjust		0-36db
16	MIC volume adjust	12 level digital volume adjust		0-36db
17	Electric lock control		1	Relay control
18	PC on-off control		1	Relay control
19	Can control power output	Intn'l standard mains socket	3	AC220V/10A (Projector, Amplifier, Other)
20	Control motor screen up/down	American standard mains Socket	1	AC220V/10A
21	Power input	1.5 meters	1	AC220V \pm 15% 10A 50Hz
22	Weight			8kg
23	Dimensions	Host:445(L)*270W*88H mm Panel:220(L)*133W*90H mm		
24	Power consumption			30W
25	Storage temperature			-25 -50 $^{\circ}$ /5% -85% (No dew)
26	Operating temperature			0 -40 $^{\circ}$ /10% -80% (No dew)

abichina

Distributed by: ABI China Ltd. 8F/122-124 Connaught Rd, Central, HONG KONG
Tel: 852.2543 8420 Fax: 852.2544 9359 Email: info@abichina.com
www.abichina.com